

CUSTOM SPIN

- Multi-disc, Japanese oiled felt drag system
- 5+1BB bearings drive system
- Quick-Set anti-reverse roller bearing
- Precision machine cut brass pinion gear
- Corrosion-resistant graphite body
- Precision Elliptical Gearing System
- Machined aluminum, 2-tone anodized spool
- RESII: Computer-balanced Rotor Equalizing System
- Metal handle with EVA knob
- LCS line control spool



ITEM NO.	MODEL	DRAG POWER	GEAR RATIO	LINE CAPACITY	LINE RETRIEVE	WEIGHT	PRICE
54236*	CSP-10	3kg	5.0:1	260m/0.10mm	53cm	171g	-
54237	CSP-25	3kg	5.0:1	360m/0.15mm	63cm	230g	-
54238	CSP-30	3kg	5.0:1	240m/0.20mm	63cm	230g	-
54239	CSP-40	6kg	5.0:1	300m/0.25mm	73cm	270g	-
54240	CSP-55	9kg	4.5:1	380m/0.30mm	76cm	360g	-
54241	CSP-65	11kg	4.8:1	390m/0.35mm	91cm	575g	-
54242	CSP-80	11kg	4.8:1	305m/0.45mm	101cm	600g	-

*4+1BB

Pack Size: 1

ALARIS SPINNING

- Multi-disc, Japanese oiled felt drag washers
- 3BB+1RB ball bearings drive
- Quick-Set ant-reverse bearing
- Precision machine cut brass pinion gear
- Corrosion resistant graphite body and rotor
- CFR: Cyclonic Flow Rotor technology
- Rigid metal handle design for strength
- Machined aluminum, 2-tone anodized spool with LCS lip
- Corrosion-resistant stainless steel bail wire
- RESII: Computer balanced Rotor Equalizing System



Model: ALS-40 Wide Rotor



ITEM NO.	MODEL	DRAG POWER	GEAR RATIO	LINE CAPACITY	LINE RETRIEVE	WEIGHT	PRICE
57726	ALS-20	5,4kg	4.8:1	0.15/250,0.20/140,0.25/90	61cm	204g	-
57727	ALS-30	7,2kg	5.0:1	0.20/300,0.25/200,0.3/130	71cm	237g	-
57728	ALS-40	7,9kg	5.0:1	0.25/260,0.30/180,0.35/130	85cm	260g	-

Pack Size: 1